



A4 cut protection with enhanced grip and liquid resistance. The 13-gauge construction provides good dexterity and flexibility, while the three-quarter nitrile coating helps protect against water and oil. A sandy nitrile palm finish delivers reliable grip in dry and oily working conditions.

KEY FEATURES

- **13-gauge construction** provides good dexterity and flexibility.
- **Water and oil repellent construction** helps keep hands protected in wet and oily work environments.
- **Sandy nitrile palm finish** delivers reliable grip in dry and oily working conditions.
- **Contact heat protection up to 100°C** according to EN 407.

ANSI / ISEA 105-2024

A4  
6 4

A4

6

4

EN388  
4X44D

EN407  
X1XXXX

13  
Gauge

SPECIFICATIONS

|                   |                         |
|-------------------|-------------------------|
| Color             | Red                     |
| Sizes             | S, M, L, XL, XXL        |
| Packaging         | 1 Dozen / Polybag       |
| Packed            | 12 Dozen / Case         |
| Liner             | UHMWPE, Glass Fiber     |
| Gauge             | 13                      |
| Coating           | Nitrile                 |
| Finishing         | Sandy & Flat            |
| Coverage          | Palm and Fingers & Full |
| Coating Color     | Black & Red             |
| Cuff              | Knit Wrist              |
| Country of Origin | China                   |

PERFORMANCE DATA

|                                |        |
|--------------------------------|--------|
| ANSI / ISEA 105 Cut Level      | A4     |
| ANSI / ISEA 105 Abrasion Level | 6      |
| ANSI / ISEA 105 Puncture Level | 4      |
| EN388                          | 4X44D  |
| EN407                          | X1XXXX |

CARE INSTRUCTIONS

Recommended washing temperature is at 40°C (104°F) with mild detergent. Hang the gloves to dry thoroughly, air-dry your gloves to prevent or reduce any material shrinkage and maintain proper size, or tumble-dry with no heat.

 **WARNING** This product is cut and puncture resistant, **NOT Cut And Puncture Proof**. Do not use with moving or serrated blades or rotating equipments. User shall be exclusively responsible to assess the suitability of the product as specified for any individual application or use. Failure to follow these warnings may result in death or serious bodily injury. **California Residents: Cancer - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).**



SKU INFORMATION

| SKU       | SIZE | UPC (INNER PACK) | UPC (CASE)     | CASE DIMENSIONS (IN) | WEIGHT (LBS) | OVERLOCK COLOR |
|-----------|------|------------------|----------------|----------------------|--------------|----------------|
| 12-369-7  | S    | 810216940720     | 00810216940720 | 15.8 x 10.6 x 16.2   | 25.9         | Yellow         |
| 12-369-8  | M    | 810216940737     | 00810216940737 | 15.8 x 10.6 x 16.2   | 29.2         | Red            |
| 12-369-9  | L    | 810216940744     | 00810216940744 | 18.5 x 11.0 x 16.5   | 35.0         | Green          |
| 12-369-10 | XL   | 810216940751     | 00810216940751 | 18.5 x 11.0 x 18.1   | 38.3         | White          |
| 12-369-11 | XXL  | 810216940768     | 00810216940768 | 18.5 x 11.0 x 18.1   | 41.6         | Brown          |

